

# C321+ GNSS Smart Antenna

## GNSS Smart Antenna for Construction

key features

- RTK Base station with internal UHF radio
- UHF RTK rover
- Network RTK rover
- Multi-GNSS including GPS, GLONASS, BeiDou, QZSS, Galileo, SBAS, and L-band
- Athena™ RTK engine and Atlas® GNSS Global Correction Service
- Dual hot-swappable lithium batteries provides 12 hours of battery life
- aRTK™ capabilities - Satellite-based RTK augmentation



 atlas

---

A rugged base station for your machine control jobsite or a rover to assist with grade checking and construction staking activities.

C321+ provides users a precise base station solution for sending RTK corrections to your existing fleet of machine control systems including RTK rovers via the internal UHF radio or an external radio of your choice. The C321+ receiver can also be used as a UHF or network RTK rover receiving corrections via the internet. Market-leading GNSS technology delivered at an exceptional value make the Hemisphere C321+ the ideal receiver for your high-performance satellite positioning needs.

 Hemisphere®

[precision@hgns.com](mailto:precision@hgns.com)  
[www.hgns.com](http://www.hgns.com)

# C321+ GNSS Smart Antenna

## GNSS Receiver Specifications

Receiver Type:	GNSS Position RTK Receiver	
Positioning Modes:	RTK, Atlas, DGNS, SBAS	
Channels:	572	
RTK Formats:	RTCM3, ROX, CMR, CMR+ <sup>4</sup>	
L-Band Formats:	Atlas Basic, Atlas H30, Atlas H10	
Update Rate/ Recording Interval:	1, 2, 4, 5, 10 Hz, and 20 Hz <sup>3</sup>	

## Positioning Accuracy

Horizontal Accuracy:	RMS (67%)	2DRMS (95%)
RTK: <sup>1,2</sup>	8 mm + 1 ppm	15 mm + 1 ppm
Static Performance (long occupation):	3 mm + 0.1 ppm	3.5 mm + 0.4 ppm
Static Performance (rapid occupation):	3 mm + 0.5 ppm	5 mm + 0.5 ppm
L-Band Performance: <sup>1,3</sup>	0.08 m	0.16 m
SBAS (WAAS): <sup>1</sup>	0.3 m	0.6 m
Autonomous, no SA: <sup>1</sup>	1.2 m	2.4 m

## Satellite Tracking

GPS:	L1CA, L1P, L2P, L2C, L5
GLONASS:	G1, G2, P1, P2
BeiDou:	B1, B2
QZSS:	L1C, L1CA, L2C, L5
Galileo:	E1BC, E5a, E5b
SBAS:	MSAS, WAAS, EGNOS, GAGAN

## Communications

Connectors I/O:	5-pin Lemo connector for external power supply and external radio devices 7-pin Lemo connector for USB OTG connection and a serial port interface 1 SMA antenna connector for UHF radio 1 SMA antenna connector for UMTS Radio
WebUI:	Supports software & firmware updates, management of receiver configuration and data transfers with any Wi-Fi equipped device.
TTS:	Smart voice broadcast system "Speaking" receiver
Reference Outputs:	RTCM2.1, RTCM2.3, RTCM3.0, RTCM3.1, RTCM3.2 including MSM

## Radio

Frequency Range:	410 - 470 MHz
Channel Spacing:	12.5kHz / 25 KHz
Transmitting Power:	0.5 / 1 W

## Wireless Module

Wi-Fi:	Integrated module with internal Wi-Fi antenna
Bluetooth:	Bluetooth 2.1 + EDR Integrated Bluetooth (BT) communication module with internal BT antenna

## Cellular

PLS8-E (International):	<b>4G</b> - Penta Band LTE - 800/900/1800/2100/2600 MHz - FDD-Band (20, 8, 3, 7, 1) <b>3G</b> - Tri Band UMTS (WCDMA) - 900/1800/2100 MHz - FDD-Band (8, 3, 1) <b>2G</b> - Dual Band GSM/GPRS/EDGE - 900/1800 MHz
PLS8-X (North America):	<b>4G</b> - Penta Band LTE - 700/700/850/AWS (1700/2100)/1900 MHz - FDD-Band (13, 17, 5, 4, 2) <b>3G</b> - Tri Band UMTS (WCDMA) - 850/AWS (1700/2100)/1900 MHz - FDD-Band (5, 4, 2) <b>2G</b> - Quad Band GSM/GPRS/EDGE - 850/900/1800/1900 MHz

## Power

Battery:	Hot-swappable 11.1 V - 37.74 Wh intelligent lithium (2 per kit)
Battery life:	12 hour operation from two batteries with UHF radio in Rx mode
Voltage:	9 to 22V DC external power input with over-voltage protection (5-pin Lemo)
Charge Time:	Typically 7 hours

## Memory

SIM Card:	User accessible SIM card slot
Memory:	Internal 4 GB, accessible through USB and Wi-Fi
SD Card:	External Micro SD card slot 64 GB

## Environmental

Operating Temperature:	-30°C to 60°C (-22°F to 140°F)
Storage Temperature:	-40°C to 80°C (-40°F to 176°F)
Waterproof/ Dustproof:	IP67. Protected from temporary immersion to a depth of 1 meter MIL-STD-810G, method 516.6 Designed to survive a 2 m pole drop on concrete floor Designed to survive a 1 m free drop on hardwood floor
Shock Resistance:	MIL-STD-810G, method 514.6E-1 Up to 100%
Vibration:	UL recognized, 94HB Flame Class Rating (3) 1.49mm
Humidity:	Cleaning agents, soapy water, industrial alcohol, water vapor, solar radiation (UV)
Inflammability:	
Chemical Resistance:	

## Mechanical

Size:	14.1 D x 14.0 H (cm) 5.5 D x 5.5 H (in)
Weight:	<1.38 kgs (<3.05 lbs)
Mounting:	5/8"x11, 55° thread angle, stainless steel insert
Phase Center Offset:	GPS L1 and L2 offset below 2.5mm

- 1 Depends on multipath environment, number of satellites in view, satellite geometry, and ionospheric activity
- 2 Depends also on baseline length
- 3 Requires a subscription from Hemisphere GNSS
- 4 CMR and CMR+ do not cover proprietary messages outside of the typical standard

Authorized Distributor:

Copyright Hemisphere GNSS, Inc. All rights reserved. Specifications subject to change without notice.  
Hemisphere GNSS, aRTK, Athena, and Atlas are trademarks of Hemisphere GNSS, Inc.  
Rev. 03/19



Hemisphere GNSS, Inc.  
8515 E. Anderson Drive  
Scottsdale, AZ, USA 85255

Toll-Free: +1 (855) 203-1770  
Phone: +1 (480) 348-6380  
Fax: +1 (480) 270-5070  
precision@hgns.com  
www.hgns.com