

---

# Antennas GPS-704-X

---



MULTI-FREQUENCY ANTENNA  
DELIVERS EXCELLENT PERFORMANCE,  
MULTIPATH REJECTION AND  
L-BAND FUNCTIONALITY

---



## BENEFITS

---

- + Provides a single antenna solution for GPS L1, L2, L5, Galileo L1, E5a & b, E6, GLONASS L1, L2, BeiDou B1, B2, B3 and L-Band

## FEATURES

---

- + Access to multiple Global Navigation Satellite Systems
- 

## EXCEPTIONAL L-BAND RECEPTION

The GPS-704-X Galileo passive antenna features improved performance to ensure excellent operation in all GPS, Galileo and GLONASS frequency bands. The antenna also includes NovAtel's patented Pinwheel® technology for excellent multipath rejection and phase center stability.

If you require more information about our antennas, visit [www.novatel.com/antennas](http://www.novatel.com/antennas)



Contact NavtechGPS for product details. [www.NavtechGPS.com](http://www.NavtechGPS.com)  
+1-703-256-8900 • 800-628-0885 • [info@navtechgps.com](mailto:info@navtechgps.com)

# GPS-704-X

## PERFORMANCE

<b>3 dB Pass Band</b>	1.15 - 1.65 GHz
<b>Passive Antenna</b>	External LNA Required
<b>Gain at Zenith (90°)</b>	
L1	+6.0 dBic (minimum)
L2, B2	+2.5 dBic (minimum)
L5, E5a	+2.0 dBic (minimum)
E6, B3	+3.0 dBic (minimum)
L-Band, B1	+6.0 dBic (minimum)
<b>Gain Roll-Off (from Zenith to Horizon)</b>	
L1, L-Band, B1	14 dB
L2, E6, B2, B3	11 dB
L5, E5	11 dB
<b>VSWR</b>	≤ 2.0 : 1
<b>Nominal Impedance</b>	50 Ω
<b>Altitude</b>	9,000 m

## PHYSICAL AND ELECTRICAL

<b>Size</b>	
Diameter <sup>1</sup>	185 mm
Height	69 mm
<b>Weight</b>	468 g
<b>Connector</b>	TNC female

## ENVIRONMENTAL

<b>Temperature</b>	
Operating	-40°C to +85°C
Storage	-55°C to +85°C
<b>Humidity</b>	95% non-condensing
<b>Salt Spray</b>	MIL-STD-810F, 509.4
<b>Waterproof</b>	IEC 60529 IPX7
<b>Compliance</b>	CE
<b>RoHS</b>	EU Directive 2011/65/EU

For the most recent details of this product:  
[www.novatel.com/products/gnss-antennas/high-performance-gnss-antennas/gps-704-x/](http://www.novatel.com/products/gnss-antennas/high-performance-gnss-antennas/gps-704-x/)

## novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)  
or 403-295-4900

China 0086-21-54452990-8011

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

**Version 4** Specifications subject to change without notice.

©2014 NovAtel Inc. All rights reserved.

NovAtel and Pinwheel are registered trademarks of NovAtel Inc.

Printed in Canada.

D09449 February 2014



1. Not including tape measure tab. Full diameter with tape measure tab is 195 mm.