



The AsteRx-U is an all-in-one multi-frequency GNSS receiver with UHF radio, WiFi, Bluetooth and a L-Band receiver combined with spectrum analyzer for the broadest range of applications.

## Key Features

- ▶ **544 channels for tracking all known and future signals from GPS, GLONASS, GALILEO, BEIDOU, IRNSS, QZSS and SBAS on both antennas**
- ▶ **Precise and solid heading calculation**
- ▶ **cm-level (RTK) and sub dm-level (PPP) position accuracy**
- ▶ **Dual L-band channel with support for TerraStar corrections**
- ▶ **Septentrio GNSS+ algorithms for solid performance**
- ▶ **Integrated cellular modem, Bluetooth and WiFi optional UHF radio**

### Consistently accurate now and into the future

The AsteRx-U is powered by the AsteRx4, the most advanced multi-constellation dual antenna receiver from Septentrio. Its multi-frequency engine can track all current and future Global Navigation Satellite System (GNSS) constellations - GPS, GLONASS, Galileo, BeiDou, IRNSS and QZSS – on both antennas. This guarantees you reliable and accurate GNSS positioning now and into the future.

### Centimeter scalable accuracy

Septentrio's knowledge and experience in the GNSS industry ensures that the AsteRx-U MARINE offers you the highest possible accuracy, scalable to a centimeter. LOCK+ technology maintains tracking during heavy vibration and IONO+ technology assures position accuracy even under periods of elevated ionospheric activity. The AsteRx-U features special interference mitigation technology which filters out ambient intentional and unintentional RF interference.

### Connect with any device

Use any device with a web browser to operate the AsteRx-U without any special configuration software via the built-in webserver accessible over WIFI, network or USB connection.

## FEATURES

### GNSS Technology

544 hardware channels for simultaneous tracking of all visible satellite signals

Supported signals: GPS (L1, L2, L5), GLONASS (L1,L2,L3), GALILEO (E5ab, AltBoc, E6), BEIDOU (B1, B2, B3), IRNSS (L5), QZSS (L1,L2,L5) (Galileo, Beidou and IRNSS, are optional features)

All-in-view SBAS (EGNOS, WAAS, GAGAN, MSAS, SDCM) (incl. L5 tracking)

Integrated dual channel L-band receiver

100 Hz Raw data output (code, carrier, navigation data) (optional feature)

20 Hz SBAS, DGNSS, PPP and RTK (50 Hz available in future firmware versions)

A Posteriori Multipath Estimator Technique (APME+), including code and phase multipath mitigation

AIM+/WIMU interference mitigation unit, including chirp jammers

ION+ Advanced scintillation mitigation

RAIM

DGNSS (base station and rover)

RTK (base and rover) (base is an optional feature)

Use of TerraStar services (optional feature)

Moving base RTK positioning (optional feature)

8 GB Internal Memory; expandable with an external SD card

### Connectivity

3 hi-speed serial ports (RS232)

Ethernet port (TCP/IP and UDP)

Full speed USB (host and device)

2 Event markers

xPPS output (max. 100 Hz)

Integrated Bluetooth (2.1 + EDR/4.0)

Integrated Quadband Cellular Modem (EDGE, 2G, 3G, 3.5G)

Integrated Wi-Fi (802.11 b/g/n)

(optional) Integrated UHF (406-470 MHz)

### Formats

Highly Compact and fully documented Septentrio Binary Format (SBF) output

NMEA v2.30 output format, up to 20 Hz; NMEA 4.0; NMEA 3.01

RTCM v2.2, 2.3, 3.0 or 3.1

CMR2.0 and CMR+ (CMR+ input only)

UHF: Pacific Crest (GMSK, 4FSK, FST), SATEL, Trimtalk (450S\_P, 450S\_T)

## PERFORMANCE

### Position accuracy<sup>1,2,3</sup>

	Horizontal	Vertical
Standalone	1.2 m	1.9 m
SBAS	0.6 m	0.8 m
DGNSS	0.4 m	0.9 m
TerraStar-D <sup>4</sup>	6 cm	<10 cm

### RTK Performance<sup>1,2,3,6,7</sup>

Horizontal accuracy <sup>3</sup>	0.6 cm + 0.5 ppm	
Vertical accuracy <sup>3</sup>	1 cm + 1 ppm	
Average time to fix <sup>7</sup>	7 s	

### Velocity Accuracy<sup>1,2,3</sup>

	Horizontal <sup>3</sup>	Vertical <sup>3</sup>
	0.01 m/s	0.015 m/s

### Heading Accuracy<sup>1,2,3</sup>

	Heading	Pitch/Roll
1m antenna separation	0.1°	0.2°
10m antenna separation	0.01°	0.02°

### Maximum Update rate

Position	20 Hz (50 Hz in future firmware version)
Measurements	100 Hz

### Latency

< 20 m/s

### Time accuracy<sup>3</sup>

xPPS Out	10 ns
Event accuracy	< 20 ns

### Time to first fix

Cold start <sup>8</sup>	< 45 s
Warm start <sup>9</sup>	< 20 s
Re-acquisition	avg. 1.2 s

### Tracking performance (C/N0 threshold)

Tracking	20 dB-Hz
Acquisition	33 dB-Hz

### Dynamics

Acceleration	10 g
Jerk	4 g/s

## PHYSICAL AND ENVIRONMENTAL

**Size** 164 x 157 x 54 mm

**Weight** 1.5 kg

**Input voltage** 9–36 V DC

**Power Consumption** 7 W Typical

**Operating temperature** -30°C to +65°C

**Storage temperature** -40°C to +75°C

**Humidity** MIL-STD810G, Method 507.5, Procedure I

**Dust** MIL-STD-810G, Method 510.5, Procedure I

**Shock** MIL-STD-810G, Method 516.6, Procedure I/II

**Vibration** MIL-STD-810G, Method 514.6, Procedure I

### Connectors

Antennas TNC female

Power LEMO 4 pins female

USB/ETH LEMO 16 pins female

PPS-OUT LEMO 5 pins female

Serial 2 LEMO 9 pins female

Serial 1 and 3, USB-host LEMO 14 pins, female

Events/GPIO LEMO 7 pins, female

### Antenna LNA Power Output

Output voltage 5 V DC

Maximum current 200 mA

<sup>1</sup> 1-20 Hz measurement rate

<sup>2</sup> Performance in open sky conditions

<sup>3</sup> RMS level

<sup>4</sup> Requires service activation from TerraStar

<sup>6</sup> RTK fixed ambiguities

<sup>7</sup> Baseline: < 40 km

<sup>8</sup> No information available (no almanacs, no approximate position)

<sup>9</sup> Ephemeris and approximate position known

### Europe

Greenhill Campus  
Interleuvenlaan 15G  
3001 Leuven, Belgium

+32 16 300 800

### Americas

Suite 200,  
23848 Hawthorne Blvd  
Torrance, CA 90505, USA

+1 310 541 8139

### Asia-Pacific

Level 901, The Lee Gardens  
33 Hysan Avenue  
Causeway Bay, Hong Kong

+852 3959 8680