

KEY FEATURES

Easy to integrate rugged package

Proven Trimble GNSS technology

Industry standard D-sub connectors

Multiple configurations to suit accuracy/
price requirements

Convenience of Ethernet connectivity

RUGGED RECEIVER ENCLOSURE HOUSING A SINGLE OR DUAL TRIMBLE BD960 OEM GNSS MODULE

THE GNSS (GLOBAL NAVIGATION SATELLITE SYSTEM) INDUSTRY IS GROWING AND EVOLVING TO ADOPT NEW SIGNAL TECHNOLOGIES. BY ADOPTING MODERNIZED GPS AND GLONASS SIGNAL POSITIONING, APPLICATIONS REACH NEW LEVELS OF PERFORMANCE AND PRODUCTIVITY.

BX960 GNSS RUGGED RECEIVER ENCLOSURE

The Trimble® BX960 GNSS receiver enclosure is a multi-channel, multi-frequency, OEM GNSS receiver. Harnessing the power of the Trimble BD960 module, the receiver allows OEM's and system integrators to rapidly integrate centimeter-level positioning into their application. Industry standard D-sub connectors provide access to all power and communications. Both serial and Ethernet connectivity are supported. Multiple configurations are available from L1 DGPS to the fully loaded RTK unit tracking GPS L1/L2/L5 and GLONASS L1/L2 signals.

Industry professionals trust Trimble embedded positioning technologies as the core of their precision applications. With the latest Trimble-precise Maxwell® technology, the BX960 provides assurance of long-term futureproofing and trouble-free operation.

BX960-2 GNSS RUGGED RECEIVER ENCLOSURE

The Trimble BX960-2 GNSS receiver packages two Trimble BD960 modules in a single rugged enclosure. This allows a Moving Baseline RTK solution to be calculated between two antennas. The resulting centimeter accurate vector and heading information can be output to the serial port in ASCII or binary format. This addresses a range of precise navigation applications where both centimeter accurate positions and precise heading is required. For less demanding accuracy applications DGPS and OmniSTAR versions are available.

Both receivers were designed for easy integration and rugged dependability. Customers benefit from the Ethernet connectivity available, allowing high speed data transfer and configuration via standard web browsers. Just like other Trimble embedded technologies, easy to use software commands simplify integration and reduce development times. All software features are password-upgradeable, allowing functionality to be upgraded as your requirements change. The BX960 is rigorously tested to perform in harsh environmental conditions with the reliability you expect from Trimble.



TRIMBLE BX960 GNSS RUGGED RECEIVER ENCLOSURE

TECHNICAL SPECIFICATIONS

- Advanced Trimble Maxwell Custom Survey GNSS technology
 - High precision multiple correlator for GNSS pseudorange measurements
 - Unfiltered, unsmoothed pseudorange measurements data for low noise, low multipath error, low time domain correlation and high dynamic response
 - Very low receiver noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
 - Signal-to-Noise ratios reported in dB-Hz
 - 72 Channels:
 - GPS L1 C/A Code, L2C, L1/L2/L5 Full Cycle Carrier
 - GLONASS L1 C/A Code, L1 P Code, L2 C/A, L2 P Code, L1/L2 Full Cycle Carrier (BX960-2 contains a second 72 channel receiver configured for heading only)
 - 4 additional channels for SBAS WAAS/EGNOS/MSAS support
 - L-Band OmniSTAR VBS, HP & XP
 - 1 LAN Ethernet port:
 - Supports links to 10BaseT/100BaseT networks
 - All functions are performed through a single IP address simultaneously—including web GUI access and raw data streaming
 - Network Protocols supported
 - ▶ HTTP (web GUI)
 - ▶ NTP Server
 - ▶ NMEA, GSOFF, CMR etc over TCP/IP or UDP
 - ▶ NTRipCaster, NTRipServer, NTRipClient
 - ▶ mDNS/uPnP Service discovery
 - ▶ Dynamic DNS
 - ▶ eMail alerts
 - ▶ Network link to Google Earth
 - ▶ Support for external modems via PPP
 - BX960 has 2 x RS232 ports and BX960-2 has 3 x RS232 ports:
 - Baud rates up to 115,200
 - 1 Hz, 2 Hz, 5 Hz, 10 Hz and 20 Hz positioning and data streaming outputs
 - Reference outputs CMR, CMR+, RTCM 2.1, 2.2, 2.3, 3.0
 - Control Software:
 - HTML web browser. Internet Explorer 7.0 or later, Firefox 2.0 or later
 - PC Utilities including Configuration Toolbox
 - 1 Pulse Per Second Output
- Initialization time¹ typically <10 seconds
 Initialization reliability¹ >99.9%
 Navigation outputs ASCII: NMEA-0183 GSV, AVR, RMC, HDT, VGK, VHD, ROT, GGK, GGA, GSA, ZDA, VTG, GST, PJT, PJK and Binary: Trimble GSOFF

LED's:

- BX960 GNSS receiver enclosure 3
- BX960-2 GNSS receiver enclosure 6
(indicating Power, Satellite Tracking, and Differential Data)

© 2012, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Maxwell is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. PN 022543-465 (02/12)

POSITIONING SPECIFICATIONS

Mode	Accuracy ²	Latency ³	Maximum Rate
Single Baseline RTK (<30km)	8 mm + 1 ppm Horizontal 15 mm + 1 ppm Vertical	<20 ms	20 Hz
DGPS	0.25 m + 1 ppm Horizontal 0.50 m + 1 ppm Vertical	<20 ms	20 Hz
DGPS	<1 m 3D	<20 ms	20 Hz
SBAS ⁴	<5 m 3D	<20 ms	20 Hz

HEADING SPECIFICATIONS (BX960-2 GNSS RECEIVER ONLY)

Baseline	Accuracy ²	Maximum Rate
2 m	<0.09°	10 Hz
10 m	<0.05°	10 Hz

PHYSICAL CHARACTERISTICS

- Size 261 mm x 140 mm x 55 mm
- Power 9 V DC to 28 V DC
Maximum 8.8 W (BD960-2)
- Weight 1.6kg
- Connectors
 - I/O D-sub DE9 and DA26 (BX960-2 has an additional DE9)
 - Antenna TNC (BX960-2 has an additional TNC)

ENVIRONMENTAL CHARACTERISTICS

- Temperature
 - Operating -40 °C to +70 °C
 - Storage -55 °C to +85 °C
- Vibration MIL810F, tailored
Random 6.2 gRMS operating
Random 8 gRMS survival
- Mechanical shock MIL810D
±40 g operating
±75 g survival
- IP Rating IP67

ORDERING INFORMATION

- Module Trimble BX960 GNSS receiver enclosure available in a variety of configurations from L1 DGPS upwards

¹ May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.
² 1 sigma level, when using Trimble Zephyr 2 antennas.
³ At maximum output rate.
⁴ Depends on SBAS system performance.

Specifications subject to change without notice.



AMERICAS & ASIA-PACIFIC
TRIMBLE NAVIGATION LIMITED
 Integrated Technologies
 510 DeGuigne Drive
 Sunnyvale, CA 94085
 USA
 +1-408-481-8070 Phone
 +1-408-481-8984 Fax
 Email: sales-intech@trimble.com

EUROPE & MIDDLE EAST
TRIMBLE GERMANY GmbH
 Integrated Technologies
 Am Prime Parc
 1165479 Raunheim,
 Germany
 Phone +49 (6142) 177-2135
 Fax +49 (6142) 177-2136
 emeasales-intech@trimble.com

CHINA
TRIMBLE NAVIGATION LIMITED
 Integrated Technologies
 311 Fute (M) Road, 3/F
 Wai Gaoqiao Free Trade Zone
 Pudong, Shanghai 200131
 China
 Email: chinasales-intech@trimble.com

RUSSIA
TRIMBLE NAVIGATION LIMITED
 Integrated Technologies
 Tel: +7 495 5041081
 Email: rusales-intech@trimble.com

www.trimble.com/gnss-inertial